

Spring Hose Clamp Pliers

with locking device

85
51

The locking device keeps the clamp open and stays locked in position without the need to grip and hold onto the pliers until the user is ready to move the clamp.

One-hand release

- > rotatable tips for securely gripping the clamps in all positions
- > jaw inserts can also be rotated under load
- > extremely good leverage which allows clamps to be opened and moved easily without great effort
- > slim head design, narrow head width, and rotatable grip inserts make this an ideal tool especially in confined areas
- > detach hoses gently using the serrated jaw behind the tips
- > chrome vanadium electric steel; forged, oil-hardened



85 51 250 AF

Product Number	Packaging	↔ Inch mm		Pliers	Handles	Gripping capacity Ø Inch	Adjustment positions	⚖ lbs
85 51 250 AF	X	10 250		grey atramentized	non-slip plastic coated	2 3/4	19	0.77
85 59 250 A	Spare part grip insert assortment for 85 51 250 A / 85 51 250 AF							

Hose Clamp Pliers

for Click Clamps

85
51

Opening and closing Click Clamps does not require a special skill; it requires a special tool. No need to replace the OEM clamp with a screw clamp, these pliers will not harm the clamps they're compressing, allowing them to be reused over and over again.

- > rotating tips for reliably gripping of clamps in any position
- > high leverage allows clamps to be opened and closed again comfortably and easily without a great deal of effort
- > for easy working on fuel hoses, vacuum pipes with suction nozzles and many other applications
- > detach hoses gently using the serrated jaw behind the tips
- > slim head design, narrow head width, and rotatable grip inserts make this an ideal tool especially in confined areas
- > chrome vanadium electric steel; forged, oil-hardened



85 51 180 C



85 51 250 C



Hose clamp without limit stop



Hose clamp with limit stop



Serrated gripping jaws for easy loosening of tight hoses



Rotating tips

Product Number	Packaging	↔ Inch mm		Pliers	Handles	Diameter Ø inch Ø mm	Adjustment positions	⚖ lbs
85 51 180 C	X	7 1/4 180		grey atramentized	non-slip plastic coated	1 3/4 45	12	0.38
85 51 250 C	X	10 250		grey atramentized	non-slip plastic coated	2 3/4 70	15	0.75
85 59 250 C	Spare part grip insert assortment for 85 51 180 C / 85 51 250 C							