

Grips rusted nuts with rounded edges



Self-locking: no slipping off workpieces; less effort required



Raptor[™] Pliers as the second spanner for tightening locknuts



Fine adjustment by pushing a button: fast and comfortable

| Product Number | Packaging | ←→ Inch mm | Pliers | Head | Handles | Inch mm | Adjustment positions | ۵ ^۲ ۵ Ibs |
|----------------|-----------|-------------------------|-------------------|----------|-------------------------|-------------------------------------|-------------------------|-------------------------|
| 87 41 250 | х | <mark>10</mark> 250 | grey atramentized | polished | non-slip plastic coated | <mark>3/8 - 1 1/4</mark> 10 - 32 | 15 | 0.72 |

KNIPEX Cobra[®] ES High-Tech Water Pump Pliers, extra-slim DIN ISO 8976

87 5



Slim head and joint area

Fine adjustment by pushing a button: fast and comfortable



Optimum access to the workpiece. Ideal for service and maintenance, equipment repair, automotive and general industry



(compared to conventional water pump pliers)

Grips nuts up to 1 3/8" (34 mm) across flats

- > ideal for service and maintenance, equipment repair, automotive and general industry
- > long, narrow jaws
- > good access to the workpiece due to very slim construction of head and joint area
- > grips flat material due to three-point rest
- > adjustment at the touch of a button directly on the workpiece
- > fine adjustment for optimum adaptation to different size workpieces and a comfortable gripping position
- > self-locking on pipes and nuts: no slipping off the workpiece and low handforce required
- > box-joint design: high stability because of double guide
- > reliable catching of the hinge bolt: no unintentional shifting
- > favorable lever action: optimum transmission of force
- > pinch guard prevents operators' fingers being pinched
- > chrome vanadium electric steel; forged, multi stage oil-hardened



87 51 250

| Product Number | Packaging | ▲→ Inch mm | Pliers | Head | Handles | O∃ <mark>Ø Inch</mark> Ø mm | Inch mm | Max. parallel opening width Inch mm | Max. gripping depth Inch mm | Adjustment positions | ۵ ^۲ ۵ Ibs |
|----------------|-----------|-------------------------|----------------------|----------|----------------------------|-----------------------------------|--------------------------|----------------------------------------------|--------------------------------------|-------------------------|-------------------------|
| 87 51 250 | Х | <mark>10</mark> 250 | grey atramentized | polished | non-slip plastic coated | 1 1/4 32 | <mark>1 3/8</mark> 34 | 1 1/2 37 | 1 5/8 42 | 19 | 0.72 |